

MATTINGLY, STANGER & MALUR, P.C.

JOHN R. MATTINGLY*
DANIEL J. STANGER
SHRINATH MALUR*

GENE W. STOCKMAN
Of Counsel

JEFFREY M. KETCHUM
SCOTT W. BRICKNER
Registered Patent Agents

* Bar Membership Other Than Virginia

ATTORNEYS AT LAW

104 EAST HUME AVENUE
ALEXANDRIA, VIRGINIA 22301

(703) 684-1120

PATENT, TRADEMARK
AND COPYRIGHT LAW

FACSIMILE (703) 684-1157

Date: August 10, 2000

Attorney Docket No. NIP-189

To: Assistant Commissioner for Patents
Washington, D.C. 20231

Sir: Transmitted herewith for filing is the patent application of:

Inventor: SEE ATTACHED LIST (K. YAMAASHI et al)

For:
DIGITAL BROADCASTING SYSTEM, MOBILE
TERMINAL AND INFORMATION SERVICE STATION

Enclosed are:



9 Sheets of Drawings



This application is being filed without an executed Declaration.



Priority is claimed from Japanese Application No. 11-227255
filed August 11, 1999. ☒ A certified copy is attached herewith.



Copies of the disclosure documents listed on the attached PTO 1449 form and
☒ discussed in the specification or ☒ attached Information Disclosure Statement.



A verified statement to establish small entity status under 37 CFR 1.9 and 1.27.



Specification: Abstract ☒, Description 38 pages; and 24 claim(s).



Preliminary Amendment.



Executed Declaration.

The filing fee is calculated as shown below:

Small Entity

Large Entity

For:	No. Filed	No. Extra
Basic Fee		
Total Claims	24 - 20 = *	4
Indep Claims	3 - 3 = *	0
<input type="checkbox"/> Multiple Dependent Claim (s)		

* If difference is less than zero
then enter '0' in second column

Rate	Fee
	\$ 345
x 9	\$
x 39	\$
+ 130	\$
Total	\$

OR

Rate	Fee
	\$ 690
x 18	\$ 72
x 78	\$ 0
+ 260	\$ 0
Total	\$ 762



A check in the amount of \$ 762.00 is enclosed for the filing fee.



The Commissioner is hereby authorized to charge any additional fees that may be required to
Deposit Account No. 50-1417.

Respectfully Submitted,

By:

John R. Mattingly

Registration No. 30,293

08/10/00
JC685 U.S. PTO
09/635449
08/10/00

08/10/00
JC685 U.S. PTO

09/635449-0000

Kimiya YAMAASHI, Hitachi, JAPAN;
Masato HORITA, Hitachi, JAPAN;
Yukihiro KAWAMATA, Hitachi, JAPAN.

Masato HORITA, Hitachi, JAPAN;

Yukihiro KAWAMATA, Hitachi, JAPAN.

said digital broadcasting receive apparatus has a data separation means for identifying said ordinary data and

said index data separately among the received data groups of digital broadcasting.

9. (Amended) A digital broadcasting system of claim 1, [2 or 3,] wherein

said digital broadcasting receiver is an information relay apparatus (hereinafter referred to as "information service station"), and has a data receive means for receiving said digital broadcasting contents, and a data memory means for storing said ordinary data and said index data separately among received data groups.

12. (Amended) A digital broadcasting system of claim 10 [or 11], wherein

said information service station transmits a verification information for verifying a fact that said requester obtains an distributed information along with said download data, and acknowledges a response to said verification information, and processes a billing operation.

15. (Amended) A mobile terminal of claim 13 [or 14],
wherein

said input means has an external media input means
allowing an IC card and/or an external memory media to be
inserted, and
when a designated memory media is inserted and a download
operation is requested by said input means, said management
data stored in said information memory means are read out and
stored in an inserted memory media.

17. (Amended) A mobile terminal of claim 14 [or 15],
wherein

said communication means has a receive channel
corresponding to a transmission from a download requester as
well as a receive channel for said digital broadcasting, in
which those channels are switched in responsive to an insert
operation of said designated memory media.

21. (Amended) An information service station of claim
19, wherein said cipher key is obtained from an IC card for a
mobile terminal as a cipher key [described in claim 16].


24. (Amended) An information service station of claim 19, [20, 21, 22 or 23,] wherein

in case that data requested for download are not located in said internal memory location, said requested data are captured from said external memory location indicated by an index data contained in said requested data and downloaded onto a requester.

REMARKS

Examination is requested.

Respectfully submitted,

 #34,663
John R. Mattingly
Reg. No. 30,293
Attorney for Applicant(s)

MATTINGLY, STANGER & MALUR, P.C.
104 East Hume Avenue
Alexandria, Virginia 22301
(703) 684-1120
Date: August 10, 2000

United States Patent Application

Title of the Invention

DIGITAL BROADCASTING SYSTEM, MOBILE
TERMINAL AND INFORMATION SERVICE STATION

Inventors

Kimiya YAMAASHI,
Masato HORITA,
Yukihiro KAWAMATA.

000720" 61152960

DIGITAL BROADCASTING SYSTEM, MOBILE TERMINAL AND INFORMATION
SERVICE STATION

BACKGROUND OF THE INVENTION

5 The present invention relates to a digital broadcasting
system for providing the program and data to the mobile station
on a vehicle with digital broadcasting, and to an information
service station and a mobile terminal for storing and
distributing the program and its related data which the mobile
10 object can not received.

At present, as for the information system used on the
vehicle, map navigation systems come into wide use in the
country of the inventors. An upgrading the software of the map
navigation system , however, requires technical knowledge, and
15 it is difficult for general users to upgrade the software. In
the countries outside out country, the onboard navigation
systems are designed with a general purpose OS, and various
programs are executed on it. A map navigation system is under
developing not as a dedicated terminal like a conventional map
20 navigation system but as an onboard computer system designed
with emphasis on expandability.

An Intelligent Transportation System (ITS) is under
discussion as a next generation onboard information system. An
information service to the moving vehicle is provided actively
25 in ITS. Under the present circumstance, only transient traffic
information such as traffic jam status and expected travel time
is practically in service.

In order to meet the user's needs mentioned above and
transfer information efficiently to plural targets, such a way
30 that the user can service the data and software of the navigation
system in the onboard terminal by broadcasting the data though
digital broadcasting and/or FM broadcasting is introduced

(Japanese Patent Application Laid-Open Number 8-87234 (1996), and Japanese Patent Application Laid-Open Number 8-195690 (1996)). By integrating the network represented by GPS and Internet and the data broadcasting, a navigation system enabling various services including upgrading of the map data at the onboard terminal with a computer is proposed (Japanese Patent Application Laid-Open Number 10-153440 (1998)).

As described above, there are some proposals found here and there which enables to register the new version of the software and control its versions in the onboard terminal by using the multiplexed data broadcasting. However, as the current information transmitted from the broadcasting station is transient (or intermittent), the user can not obtain his or her necessary data when the data broadcasting is not on air. The data distribution part of the satellite and beacon systems has a limited transmission capacity. For example, the communication satellite for digital television has 20 to 30 Mbps per 1 channel. When trying to transmit massive data and programs in such a circumstance, it is impossible to transfer all the data in a short period. In trying to repeat data broadcasting including past data, the transmission efficiency is reduced, which results in the failure of providing various data services.

Owing to this circumstance, even when the user needs a new program for the onboard terminal or tries to upgrade the version of the data in order to obtain the services provided for the onboard terminal, the transmission data is reluctantly transmitted from the data distribution parts including the satellite and beacon systems. This means that it is difficult for the user to obtain his or her necessary data when the user needs it. On the other hand, as the electric power is not applied to the onboard terminal while the vehicle stops, the data can not be received. As a result, there is such a problem that, whether

1
the required broadcasting data has been broadcasted can not be even recognized, and that the data can not be obtained.

What is proposed in Japanese Patent Application Laid-Open Number 8-87234 (1996) is a system that the data is stored
5 in plural repeater stations with broadcasting and the onboard terminal of the individual vehicle picks up the data from its neighboring repeater station if required. However, if the name of the broadcasting data which could not be received at the onboard terminal is not recognized by the onboard terminal, the
10 user can not even request what he or she asks to receive from the repeater station.

So far, there is no consideration in the conventional proposals for the onboard terminal to know what data was broadcasted in past and what data could not be received.
15 Searching a mechanism for informing easily the name of the broadcasted data and so on without increasing the amount of data is a critical problem. If the name of the data (and preferably the location of the data) which should be transmitted again can be found also in the repeater station, the efficiency in the
20 transmission processing and the storage processing can be increased and the service provided in response to the request for the broadcasting data name from the onboard terminal can be realized.

25 SUMMARY OF THE INVENTION

The present invention provides a digital broadcasting system and a mobile terminal allowing to revise software and its versions easily at the mobile terminal by using a multiplex data broadcasting, and provides an information service station
30 for storing data by relaying the digital broadcasting contents and for distributing the mobile terminal requesting those contents.

The present invention to attain the object described above is characterized as a digital broadcasting system having a digital broadcasting transmission apparatus for broadcasting data groups and a digital broadcasting receive apparatus for receiving said data groups directly or indirectly through the data distribution part, in which a transmission means for multiplexing and broadcasting (for example, with time division multiplex) ordinary data to be broadcasted as present programs and index data defined as identification information of data broadcasted in past or to be broadcasted in future. The digital broadcasting described above is established by surface wave digital broadcasting or satellite digital broadcasting.

The index data include a data ID (number and/or name) of the data broadcasted in past or to be broadcasted in future, and a remote memory location from which the data can be downloaded. The number of data ID includes an original number and a revision number of data versions and, in addition, a download charge.

The digital broadcasting transmission apparatus transmits the ordinary data and the index data with their distinctive identifiers added, and the digital broadcasting receive apparatus identifies the ordinary data and the index data separately among the received data groups of digital broadcasting by referring to the identifiers.

25 The digital broadcasting receive apparatus has a judge
means for determining whether the original data are downloaded
in the apparatus itself or not by referring to the data ID in
the received index data.

In case that the digital broadcasting receive apparatus
30 is a mobile terminal, the mobile terminal displays index data
of the original data not downloaded yet, and has a download
request means for allowing to select the necessity for

1
downloading. In this case, the mobile terminal also has a
transmission means for putting out the contents requested by
the download request means, and a receive means for receiving
the digital broadcasting contents and the download data
5 selectively. The transmission means puts out the requested
contents with a public-key used exclusively for the individual
user or terminal being added.

In case that the digital broadcasting receiver is an
information relay apparatus (hereinafter referred to as
10 "information service station"), the information relay
apparatus has a data receive means for receiving the digital
broadcasting contents, a data memory means for storing the
ordinary data and the index data separately among the received
data group, an input means for accepting a download request,
15 a data management means for referring to an index data
corresponding to the requested data in case that the data memory
means does not contain the requested data, and directing the
requested data to be retrieved from the remote memory location
specified by the index data, and a distribution means for
20 transmitting the download data to the requester. In addition,
the apparatus has also a security management means for
encrypting the download data by using a cipher key obtained from
the requester.

The information service station transmits a verification
25 information for verifying the fact that the requester obtains
the distributed information along with the download data, and
acknowledges the response to the verification information, and
processes a billing operation based on the download charge.

The digital broadcasting receive apparatus forms a
30 critical part of the digital broadcasting system of the present
invention as well as provides an invention having progressively
and novelty generic to the broadcasting receive apparatus

itself. Other features, not mentioned above, for the mobile terminal and the information service station as embodiments of this receive apparatus are shown below.

The mobile terminal of the present invention for
5 achieving the above described object as an apparatus embedding
a computer executing plural installed software programs has a
communication means for receiving digital broadcasting
contents, an input means for accepting an operation input by
the user, an information memory means for storing the programs
10 and related data, a display means for displaying the execution
result of programs and the operation screens, and a control
means for managing the program and data captured from the
communication means and the input means, in which the
information memory means stores the management information
15 including the information ID's independently of the programs
and data.

When the control means receives the index data including
data ID's (number and/or name) of the data already broadcasted
or to be broadcasted in the future along with the ordinary data
20 including the programs and related data as the time division
multiplex data of the digital broadcasting contents through the
communication means, the control means extracts the data ID's
of the data not yet downloaded among the data covered by the
index data by referring to the management data stored in the
25 information memory means, and only the data with the extracted
data ID's are displayed with the display means.

The input means has an external media input means allowing
IC cards or any type of external memory media to be inserted,
and when a designated memory media is inserted and a download
30 operation is requested by the input means, the management data
stored in the information memory means are read out and stored
in the inserted memory media. The designated memory media is,

for example, an IC card or a magnetic card, which stores the mobile terminal number and/or user number, and the cipher key for download operation.

5 The communication means has a receive channel corresponding to the transmission from the download requester as well as a receive channel for the digital broadcasting, in which those channels are switched in responsive to the insert operation of the designated memory media. This switching operation is activated with the download request by the input
10 means or the insert operation of the IC card and so on.

The information service station of the present invention for achieving the above described object stores the data groups received in the digital broadcasting and distributes the data in responsive to the download request from the mobile terminal,
15 which obtains the individual cipher key for each mobile terminal and encrypts the data requested for download by the cipher key and sends the encrypted data to the requester.

The management data including data ID's (number and/or name) of the stored data and the internal memory locations are
20 stored, and the data ID's and index data including the external data memory locations for the data already broadcasted or to be broadcasted in the future are stored as the management data. The cipher key is obtained from the output of the transmission means of the mobile terminal as described above.

25 In turn, in case that the information service station obtains the cipher key from the IC card for the mobile terminal described above, the data ID of the data already downloaded by the mobile terminal and stored in the IC card and the management information are compared with each other, and the data already
30 downloaded or the version of the data are displayed selectively.

In case that the download request is issued for the data or the version of the data displayed so far, the download charge

is further displayed so as to enable to verify the download operation. In case that the data requested for download are not located in the internal memory location, the requested data are captured from the external memory location indicated by the index data contained in the requested data and downloaded onto the requester.

According to the present invention as described above, as the mobile terminal can receive the data groups of the programs and the related data and the individual index data (identification information for tabulating the data groups) of the data groups already broadcasted or to be broadcasted in the future, both in the time division multiplex digital broadcasting contents, the data which are not obtained by the mobile terminal can be easily recognized by referring to the index data, and the download request can be issued by specifying the designated data name.

According to the present invention, as the information service station can receive and stores temporarily the data groups and the index data in the time division multiplex digital broadcasting contents, and distributes them in responsive to the download request from the mobile terminal, the data which the mobile terminal failed to receive due to its disability can be downloaded anytime. Thus, by means that the information service stations used as relay stations are distributed geometrically, the digital broadcasting station does not need to communicate directly to the individual users, and various type of data can be efficiently transmitted and the data which the mobile terminal failed to receive can be delivered at a proper timing.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic diagram of a mobile information

service system of one embodiment of the present invention.

FIG. 2 is a structure diagram of broadcast data to be multiplexed from a data transmission station.

FIG. 3 is an explanatory drawing of memory and management operations of receive information on the onboard terminal.

FIG. 4 is an explanatory drawing showing an example of screen image on the onboard terminal.

FIG. 5 is an explanatory drawing of memory and management operations of received information at the information service station.

FIG. 6 is a system block diagram including structures required for download added on the information service station and the onboard terminal.

FIG. 7 is a data structure diagram showing an example of data in the IC card.

FIG. 8 is a transition diagram of operation screens when servicing information from the information service station.

FIG. 9 is an explanatory drawing of operation screens when downloading information directly from the onboard terminal.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Now, the preferred embodiment of the present invention is described in detail by referring to the attached figures. It is difficult for users to obtain their necessary data and programs at their preferential time from the data distribution part with the onboard terminal in the prior art. In order to solve this problem, there is such a solution that the data distribution part is so configured as to enable to communicate interactively with the onboard terminal and accept requests from the onboard terminal. There are 10000000 or more vehicles in Japan, and thus, it is difficult to broadcast massive data to the individual vehicles simultaneously. Though it is

possible in practice to make the onboard terminal connect to the Internet through PDC interface of cellular phone systems and download data, it is not easy for public users to install data and programs, and revise their versions.

5 In the mobile terminal information service system of the present invention, an information service station for storing programs and data served to the onboard terminal through digital broadcasting and distributing (selling) them to the onboard terminal is provided. The information service station stores
10 massive programs and data which can not be loaded only on a single onboard terminal, and downloads them onto the onboard terminal in responsive to the request by the user through radio wave communication in the similar manner to the purchase of gasoline for the vehicle. It will be appreciated that the user can obtain
15 his or her necessary data at his or her preferential time even when the data distribution part does not distributes those data in real time.

FIG. 1 illustrates a schematic diagram of a mobile information service system of this embodiment. The mobile
20 information service system is composed of major three parts. The onboard terminal 103 is mounted on a mobile body such as vehicle 105 for providing service information to people getting in the vehicle. The data transmission station 101 distributes the information (display data and programs for the onboard
25 terminal) directed to the onboard terminal 103 to the ground station (onboard terminal 103 and information service station 104) through the data distribution part 102 such as satellite and vehicle-to-road communication path (beacon) on the road. The information service station 104 sells the data (map data,
30 music data and so on) used in the onboard terminal 103 and the programs (navigation programs and so on) used in the onboard terminal 103, and updates the version of data and programs.

The data transmission station 101 is composed of DS control part 111 for controlling totally the transmission station, DS memory part 114 for storing the information to be distributed including the program used in the onboard terminal 103, the program difference information used for version upgrade, the data (map information, shopping information and so on) used by the programs in the onboard terminal 103, DS schedule memory part 112 for storing the transmission timing (transmission schedule) for those service information, DS security management part for encrypting data for distributing data with security protection, and DS data transmission part 116 for modulating and transmitting encrypted data on a designated radio wave.

DS data control part 111 reads a time schedule stored in
15 DS schedule memory part 112 defining what information of program
files and data files in DS data memory part 114 should be sent
at each time slot. The time schedule is examined with finer time
mesh and the information file to be sent is searched, and the
information file to be sent is extracted from DS data memory
20 part 114 at a designated time before the information file is
to be transmitted, and the information file to be sent is
encrypted with a designated cipher key at DS security management
part 115, and the encrypted transmission information and the
transmission time are coupled together and made sent to DS data
25 transmission part 116. DS data transmission part 116 searches
a pair of the encrypted transmission information and the
transmission time sent from DS control part 111, and when the
scheduled transmission time is detected, then DS data
transmission part 116 modulates the encrypted transmission
30 information scheduled to be sent at this time at a designated
frequency and sends it in radio wave forms.

The data distribution part 102 is composed of a data

receive part, a data amplifier part and a data transmission part (not shown in the figure.) The encrypted transmission information sent from the data transmission station 101 is received and modulated at the data receive part, and the modulated signal is amplified by the data amplifier part, and then, the data transmission part modulates again the amplified signal at a designated frequency and resends it in radio wave forms.

The onboard terminal 103 is composed of an onboard control part 131 for controlling totally the onboard terminal, an onboard transmission and receive part 136 for receiving the transmission information (programs and data used in the onboard terminal) from the data distribution part 102 and the information service station 104, a onboard security management part 135 for managing the overall security, an onboard input part 132 for capturing the input operation by the user and programs and data through an IC card and removable media such as CD-ROM and DVD into the onboard terminal 103, an onboard memory part 134 for storing programs and data used in the onboard terminal from the onboard input part 132 and the onboard transmission and receive part 136, and an onboard display part 133 for displaying the execution result of programs (for example, car navigation screens) and operation screens to the user.

The programs and data used in the onboard terminal are read out from the removable media driver such as CD-ROM and DVD in the onboard input part 132 and stored as program files in the onboard memory part 134 by the command for requesting the execution of the program install in the media from the onboard input part 132 to the onboard control part 131. By means that the user requests the execution of the program files from the onboard input part 132, the onboard control part 131 extracts the program file corresponding to the program requested to be

executed by the user from the onboard memory part 134 and executes it.

The programs and data used in the onboard terminal to be stored in the onboard memory part 134 are obtained from the
5 information transmitted as a radio wave from the data distribution part 102 and/or the information service station 104. The onboard transmission and receive part 136 always detects a radio wave having a designated frequency like digital TV, and extracts a encrypted transmission information from the
10 data distribution part 102 and/or the information service station 104, and when a set of logical information is established, then it is transferred from the onboard transmission and receive part 136 to the onboard security management part 135. The onboard security management part 135
15 holds a key for encoding the encrypt for the encrypted transmission information received at the onboard transmission and receive part 136, and decodes the encrypted transmission information into the original transmission information with this key and transfers it to the onboard control part 131. If
20 the onboard security management part 135 can not decode the encrypted transmission information, (that is, it has no encoding key), the received information is abandoned.

The onboard memory part 131 holds temporarily the decoded transmission information in the onboard memory part 134. As the
25 area for storing the decoded transmission information inside the onboard memory part 134 is limited, if the volume of the decoded transmission information exceeds the size of this area, older one of the decoded transmission information already stored in this area is deleted sequentially according to its
30 access history, And furthermore, the onboard control part 131 displays a small icon on the onboard display part 133 the label of which is named after the name of the program captured by the

onboard transmission and receive part 136. With this user interface, the user can be made recognize that a new information is arrived and stored in the onboard memory part 134.

The information service station 104 is composed of SS control part 146 for controlling totally the station, SS data receive part 141 for receiving the encrypted transmission information from the data distribution part 102 and so on, SS memory part 147 for storing the received data, SS input part 142 for capturing the user input through an IC card and/or a touch panel into the information service station 104, SS information distribution part 144 for distributing the information in SS memory part 147 to the onboard terminal 103 of the vehicle 105 through a radio wave in responsive to the user input, SS security management part 145 for encoding the information from SS data receive part 141 and encrypting the information in SS memory part 147 to be distributed from SS information distribution part 144, and SS display part 143 for displaying the execution status of the information service station 104 and its user operation menu.

SS control part 146 inside the information service station 104 captures the download target and the encryption code for permitting the download operation in responsive to the user input (which may be allowed through an IC card as described later) from SS input part 142. A list of software available for download for the user is displayed on SS display part 143, and the user is allowed to select the data he or she wants to download. When the user specifies the data he or she wants to download, SS control part 146 extracts the specified data from SS memory part 147, and the data is encrypted by the encryption code assigned to the individual download operation defined as described above, and the encrypted data is modulated at a predefined frequency for the individual download operation and

distributed to the onboard terminal 103 by SS information distribution part 144.

As the onboard transmission and receive 136 in the onboard terminal 103 is staying in the download operation under the control of the onboard input part 132, it does not detect a radio wave from the data distribution part 102, but detects a radio wave having a frequency assigned for the information service station 104, and thus, can receive the data from SS information distribution part 144. In addition, the data received at the onboard transmission and receive part 136 is decoded by the onboard security management part 136 as described above and stored in the onboard memory part 134.

As described above, by using the information service station 104, the onboard terminal 103 can download its necessary information anytime when the user requests it. However, as the information transmission rate (band width) of the artificial satellite and the on-road communication apparatus (beacon) provided as the data distribution part 102 is limited, it is difficult to transmit all the requested data all the time. In addition, it is difficult for the onboard terminal and/or the information service station as a receiver to receive all the channel (corresponding to a single frequency or a single channel in case that a single frequency is used and multiplied in a time division mode like digital TV.) This means that the onboard terminal 103 can not obtain the information name required for allowing the user to specify the download information only by the above described architecture. In addition, the information service station can not store efficiently various information for the onboard terminal and provide the information service to be distributed.

In the system of this embodiment, the name of data already broadcasted and to be broadcasted in the future and the index

information related to their memory locations are transmitted in a time division multiplex so as to be accessible and downloadable from the remote sites.

FIG. 2 illustrates data formats of broadcast data in this embodiment. As shown in FIG. 2 (a), in addition to the ordinary data 212 and 216 broadcasted at the present time, the index information 202 is inserted in a time division multiplex. As shown in FIG. 2 (b), in the index information 202, the memory location 223 for the individual data is defined in terms of FTP (File Transfer Protocol) file directory, and its data No. 221 and data name 222 are also described. It also includes the amount of money charged to the user for the individual download operation, the comment 225 for the individual data and the broadcast time 226 of the data, which are stored in the data memory part 114 of the data transmission station 101.

In the schedule data in DS schedule memory part 112, an information for transmitting the index information 202 as well as programs and data used in the onboard terminal is defined. DS control part 111 transmits data in obedience to this index information. For example, in case that there is such a schedule data defined in DS schedule memory part 112 that the program (1) 212 is transmitted at first, the index information 202 is transmitted next, and then the program (2) 216 is transmitted, DS control part 111 extracts the data related to the program (1) from DS data memory part 114 at first, and this data is encrypted by DS security part 115 and then transferred to DS data transmission part 116. Next, DS control part 111 extracts the index information 202 from DS data memory part 114, and this data is encrypted also by DS security part 15 and then transferred to the data transmission part 116. This procedure is applied similarly to the program (2).

On the other hand, DS data transmission part 116 applies

sequentially frequency modulation to the encrypted data transmitted from DS control part 111 and transmits it. And thus, the index information 202 is inserted between the ordinary data 212 and 216 broadcasted at the moment in the data supplied from the data transmission station as shown in FIG. 2 (a). At this time, the data transmission part 111 adds the identifiers 211, 213 and 214 to the data and transmits them. This identifier contains concretely a data number 221 represented in 62 bits. A number 0 is assigned in the identifier 213 for the index information 202. Thus, whether the transmit data contains the index information 202 or the ordinary data can be recognized easily by the receive side.

As described above, by means of multiplex broadcasting of the current broadcasting program as well as the index information 202 with a fewer transmission volume, the user can recognize the existence of his or her necessary programs and/or data and their location. The user can obtain his or her necessary information not stored in the information service station 104 owing to its circumstances or not broadcasted yet by accessing through the network to the location directed by the memory location 223 in case that the information is not stored in the information service station 104.

FIG. 2 illustrates a format of the data No. in the index information. The version of programs and data executed in the onboard terminal 103 is upgraded with time. Therefore, a version upgrade of data is not definitely recognized only by means of marking serial numbers to programs and data sequentially as the broadcast programs are distributed on schedule. In this embodiment, the data No. 221 is defined with a revision No. 2212 coded in 16 bit as well as a source data o. 2211 coded in 32 bit. In addition, a associated-OS No. 2213 coded in 12 bit is allowed to be assigned in order to handle a single program title

associated with different OSs.

With this format, the information service station 104 and/or the onboard terminal 103 can recognize the source data and its version associated with the received data only by referring to the data No. 221. In case that the version upgrade data of the source data is transmitted as difference data, all the difference data associated with the source data can be obtained by using its source data No. 2211 and associated-OS No. 2213 as search keys.

Next, the operation of the onboard terminal in this embodiment is described. As the onboard terminal 103 of the mobile information service system receives the information from the data transmission station 101 as the data and its index information 202 broadcasted in the present time thorough the data distribution part 102, the user can understand what programs have been already broadcasted and what programs are to be broadcasted in the future, and even what programs he or she failed to watch.

FIG. 3 illustrates a structure of memory and management operations of the receive information at the onboard terminal. The onboard memory part 134 is composed of the onboard data management table 310 and the onboard data memory part 302. The onboard control part 131, when it receives the information originated from the data distribution part 102 from the onboard transmission and receive part 136, decodes the received information with the decode key in the onboard security management part 135, and decomposes it into parts each corresponding to the individual data, and stores them in the onboard memory part 134. At the same time, the following procedures are applied to the onboard data management table 301.

As in the case with the index information 202, what stored on the onboard data management table 301 include the data No.

321 and the data name 322 uniquely assigned to the individual data, the remote file name 323 directing the remote location in which the data files are stored, the local file name 324 with which the data file is stored locally inside the onboard terminal 103, and the amount of money charged for the individual download operation, the broadcast time 326 of the individual data and the access time 327 by the user.

Every time when the onboard control part 131 receives the individual data, it confirms the identifiers 211, 213 and 214. When the index information 202 with its identifier 0 is received, by making a comparison between the data No. 221 and the data No. 321 on the onboard data management table 301 currently stored, in case that it is proved to detects an arrival of new data, a data No. 221, a data name 222, a remote file name 223, a charge 224, a comment 225 and a broadcast time 226 of the new data are extracted from the index information 202 and added on the onboard data management table 301. At this time, NIL is put into the corresponding local file name 324 and the time 327.

In case that the index of the received data is not 0 (for receiving the data), the onboard terminal 131 searches the onboard data management table 301 by using the data No. 221 in the received data for the search key, and whether there is a local file corresponding to the data No. 321 is judged. In case that there is a local file name 324 (not NIL), the received data is abandoned. On the other hand, in case that the local file name 324 is NIL, the received data is made stored in the onboard data memory part 302 as data, and the file name (generated from the data name) stored in the onboard data memory part 301 is made stored as the local file name 324 in the onboard data management table 301. In addition, the time when the data is stored is made stored as the time 327 in the onboard data management table 301.

In case that the empty area of the onboard data memory part 302 is so small that the received data can not be stored, the onboard control part 134 deletes the data already stored and reserves the memory area on the onboard data memory part 302 for storing the next received data. At this time, the onboard control part 134 refers to the time 327 in the onboard data management table 301, and deletes older data in order of their time stamps in order to reserve the memory area for the new download data. Then, the received data is made installed. The time when the user down load the individual data is recorded as the time 327. Thus, the older data in the onboard data memory part 302 to which the user accessed in the past are deleted in order of access history.

FIG. 4 illustrates an example of the screen image of the onboard terminal. In responding to the user's selection of the data tabulation button 414 from the onboard input part 132 of the onboard terminal 103, a data table 415 including a data broadcasting menu as shown in FIG. 4 is displayed. When the data tabulation button 414 of the onboard input part 132 is selected by the user, the onboard control part 131 searches the onboard data management table 301, and recognizes the individual data status (for data No 321 judged from data No. 221, for name 322 judged from data name 222, for broadcast time 326 judged from broadcast time 226, and whether the individual data is already downloaded or not judged with local 324 being NIL or not, respectively), and then displays the data table 415 shown in FIG. 4. The data already downloaded and the data not downloaded yet are classified with their status "settled" or "unsettled", which can be recognized explicitly by the user. With this representation, the user can understand what data has been downloaded and what data has not been downloaded yet.

The user can delete, download and reserve the data in the

onboard terminal 103 by using the buttons of the onboard input part 132 shown in FIG. 4. For example, suppose that the user select the data already received shown in the data table 415. If the user select the data deletion button 402 next, similarly
5 as in the case of the data overflow described above, the onboard control part 131 deletes the substantial data (for example, the program 303) of the selected data, and initializes the local file 324 and the time 327, both corresponding to this substantial data in the onboard data management table 301 so
10 as to be NIL. In case that the user selects the data already received and selects the download button 413, he or she can download the selected data from the information service station 104 as described later.

Next, the structure and operation of the information
15 service station 104 are described. At first, the method for storing and controlling the information in the information service station is described. The information service station 104 receives the information from the data transmission station 101 through the data distribution part 102. SS control part 14
20 receives the information transmitted by the data distribution part 102 at SS data receive part 141, and then encodes the information with the decoding key in SS security management part 145, and decomposes the encoded information into parts each corresponding to the individual data and stores them into SS
25 memory part 47.

FIG. 5 illustrates the structure of SS data memory part. SS memory part 147 is composed of SS data management table 501 and SS data memory part 502. As in the case of the index information 202, what are stored in SS data management table
30 501 include the data No. 512 and the data name, both uniquely assigned to the individual data, the remote file name 523 directing the remote location in which the data files are stored,

the local file name 524 with which the data file is stored locally inside the information service station 104, and the amount of money charged for the individual down load operation, the user's access time 526 and the comment 527 for the individual data.

5 When SS control part 146 receives the index information 202, it compares the data No. 221 with the data No. 521 presently stored in SS data management table 501, and if it is judged that there is a new data, SS control part 146 extracts the data No. 221, the data name 222, the remote file name 223, the charge
10 224 and the comment 225 of the new data from the received data and adds those to SS data management table 501. At this time, the entities for the corresponding local file name 524 and time 525 are set to be NIL.

 When SS control part 146 receives the data, it searches
15 SS data management table 501 by using the data No. 221 in the received data for the search key, and whether there is a local file corresponding to the data No. 221 (= 521) is judged. In case that there is a local file name 524 (not NIL), the received data is abandoned. On the other hand, in case that the local
20 file name 524 is NIL, the received data is made stored in SS data memory part 502 as data(for example, program (1) 503), and the file name (generated from the data name) stored in SS data memory part is made stored as the local file name 524 in SS data management table 501. In addition, the time when the data is
25 stored is made stored as the time 526 in SS data management table.

 In case that the empty area of the onboard data memory part 502 is so small that the received data can not be stored, SS control part 146 deletes the data already stored and reserves the memory area on SS data memory part 502 for storing the next
30 received data. At this time, SS control part 146 refers to the time 526 in SS data management table 501, and deletes older data in order of their time stamps in order to reserve the memory

area for the new download data. The time when the user download the individual data is recorded as the time 526. Thus, the older data in SS data memory part 502 are deleted in order of history with reference to the time 526.

5 Next, methods for downloading data from the information service station 104 and data maintenance are described. FIG. 6 illustrates a structure for downloading the data from the information service station to the onboard terminal.

10 As shown in FIG. 6, the onboard input part 132 of the onboard terminal 103 has a download button 435 and an IC card reader 436. The onboard transmission and receive part 136 is composed of a channel selection part 431 for selecting a frequency with which an information the user requires is provided and/or a channel provided by multiplying a designated
15 frequency in a time division mode like digital TV, a radio wave receive part 432 for receiving a radio wave, and an antenna 433 for transmitting and receiving the radio wave.

20 When the user inserts the IC card 437 into the IC card reader 436, all the information in the IC card 437 are stored in the onboard memory part 134. At this time, if the user pushes the download button 435, the IC card 437 is ejected from the IC card reader 436. At the same time, the onboard control part 131 of the onboard terminal 103 is switched into the process in download mode. That is, the onboard control part 131
25 temporarily saves the channel number currently selected by the user in the onboard memory part 134. The onboard control part 131 requests the channel selection part 431 to switch the communication channel established in advance to the information service station 104 into receive channel mode. With this
30 operation, the onboard terminal 103 can receive an information transmitted from the information service station 104.

FIG. 7 illustrates a data structure inside the IC card.

IC card 437 has a customer data management table 601 and a registration data management table 603, and an onboard terminal No. 611, a user No. 612, a vehicle No. 614, a credit No. 616, a download public-key 620 and so on are registered in the customer data management table 601. On the other hand, the registration data management table 603 administrates the data representing the contents of programs and data groups currently downloaded in the onboard terminal 103 such as a data No. 631 (321) and a data name 632(322).

On the other hand, as shown in FIG. 6, SS input part 142 of the information service station 104 has an IC card reader 444 and a touch screen 443 on SS display part. SS data receive part 141 has SS wire communication part 442 for communicating an information through the network 402 as well as SS radio wave communication part 441 for communicating an information with a radio wave from the data distribution part 102 as described so far. The network 402 is connected to the remote distribution part 401 represented as a memory location (remote file name) 223 defined in the index information 202, and storing the source data from the data distribution part 102 and distributing the data in responsive to the request by the information service station 104.

FIG. 8 illustrates procedures (1) to (7) for screen operations when providing an information from the information service station to the onboard terminal. As shown above, when the IC card 437 ejected from the onboard terminal 103 with its mode switched to a download mode is inserted into the IC card reader 444 of the information service station 104 by the user, a procedure for providing an information by the information service station 104 is started.

When the IC card 437 is inserted into the IC card reader 444 of SS input part 142, its insertion event is reported to

SS control part 146. SS control part 146 receiving this report extracts the user name 613, the vehicle No. 614 and the password 619 from the customer data management table 601 stored in the IC card 437 thorough the IC card reader 444. A start-up screen
5 (1) generated by using the user name 613 and the vehicle No. 614 is displayed on SS display part 143, and the user's input of his or her password is expected. When the user inputs his or her password requested on the start-up screen (1) from SS input part 142, SS control part 146 compares the input password
10 and the password 619 extracted from the IC card 437. If those passwords are matched each other, the top menu (2) is displayed. If those passwords are not matched each other, the start-up screen (1) is displayed again and the user is requested to input his or her password.

15 At the top menu (2), a selection menu including "install new software", "version-up" and so on is displayed. In addition, recommendation announces to the user may be displayed. In order to prepare those display contents, SS control part 146 refers to the registered data management table 603 representing the
20 contents of programs and data groups stored in the IC card (403) and currently downloaded in the onboard terminal 103. the source data No. 2211 and the revision No. 2212 are obtained in the data No. 321 on the registered data management table. In order to judge whether there is any data with its version being able to
25 be upgraded found in the data in the onboard terminal 103, SS data management table 501 in the information service station 104 is searched by using the individual source data No. 2211 for the search key. If there found a new data in SS data management table 501 with its version higher than the version
30 of the data in the onboard terminal 103, the information indicating that "the version of program is upgraded" in the onboard terminal 103 is displayed and the user is advised to

download its new version.

When the user touches the menu indicating "new software installation" on the top menu (2) with his or her finger, the coordinate of the position at which he or her specifies on the touch panel 433 at SS input 142 is captured. SS control part 146 judges from the input coordinate that the menu indicating "new software installation" is selected, and a new software installation screen (3) is displayed in the following procedure.

SS control part 146 all the data other than the data with their data No. 321 read out from the IC card 437 and downloaded in the onboard terminal 103 are searched among the data with their source data No. 2211 corresponding to the data No. 521 stored on SS data management table 501 in the information service station 104. In addition, the searched data are sorted for the individual source data No. 2211, and the largest revision No. 2212 is found in the sorted data, and thus, program names with their revision numbers as candidates to be installed newly are displayed at SS display part (143) as shown in the screen (3.)

Collecting the individual data numbers 521 having an identical source data No. 2212 and referring to the charge 525 (which is amount of money charged for upgrading a version from its previous version for the individual data. A base charge for the program is defined for the charge for the version 0.) in SS data management table 501, the total amount of money for the data from the first version 0 to the current version is displayed for the total charge at SS display part 143.

In case that a comment 527 is stored for the latest version for the source data No. 2211 in SS data management table 501, SS control part 146 displays its comment on the comment field on the screen (3). In the illustrated example, a comment

indicating "3D image generation" is displayed on the comment field for "Navigation 1" as the first software.

The user can select his or her necessary software only by touching the title of the software on the new software installation screen (3), that is, through the touch screen 443 on SS display part 143. SS control part 146 identifies the software to be installed on the basis of the position on which the user touch. For example, in case of the screen (3), it is assumed that the user selects the title of "Navigation 1". As a matter of course, the user is allowed to select plural titles of software. When the user selects plural titles of software and presses "OK" button, SS input part 142 recognizes from the position on the touch panel that the user presses "OK" button, and displays a list of selected titles of software as shown in the download start screen (5).

In order to display the screen (5), SS control part 146 searches SS data management table 501 with the title of software selected by the user, and calculates the individual download charge for the individual software and their total charge by the above described method. In the illustrated example, "navigation 1 is ¥3,000", "WWW is ¥100" and those total charge is ¥3,100 is displayed on SS display part 146. When the user selects "Download" button, a download-on-go screen (6) is displayed next.

When the user selects "Download" button on the screen (5), SS control part 146 refers to SS data management table 501, and obtains the memory locations for designated software (for example, "Navigation 1" and "WWW".) At this time, in case that the memory location is already stored in SS memory part 147, the local memory location 524 can be obtained. On the other hand, in case that the memory location has not stored yet in SS memory part 147 or that the program content has not broadcasted yet,

the local memory location can not obtained, and hence, SS control part 146 can obtain the remote memory location 523 broadcasted as the index information 202. In case that there is an information to be downloaded at the local memory location
5 524, SS control part 146 extracts an information to be downloaded from a designated location (with a designated file name) at SS data memory part 502.

On the other hand, in case that there is an information to be downloaded at a remote site, SS control part 146 directs
10 SS data receive part 141 to get the information from the location 523 defined in SS data management table 501. SS data receive part 141, receiving the receive request and the remote site location from the SS control part 146, obtains the information to be download from the remote site, for example, the remote
15 information distribution part 401 through the network 402 with FTP protocol at SS wire communication part 442 inside SS data receive part 141. The source data already broadcasted as well as the source data to be broadcasted are ordinarily stored in the remote information distribution part 401 so as to be ready
20 for distribution.

And furthermore, SS control part146 downloads the file received from the remote site and/or the local file into the user's onboard terminal 103. When SS control part 146 obtains the information specified by the user so as to be downloaded
25 from SS memory part 147 and/or SS data receive part 141, a verification and administration number (64bit fixed-length record) uniquely assigned to the data is added onto the header of the data and encrypted with a download public-key 620 read out from the IC card 437 at SS security management part 145.
30 The encrypted information is modulated with a predefined download frequency and broadcasted at SS information distribution part 144. In order to present the progress status

of the download operation, SS control part 146 generates such a slide bar as the screen (6) with the amount of data to be downloaded and the amount of data already downloaded and displays it on SS display part 143.

5 As the channel selection part 431 in the onboard transmission and receive part 136 is tuned to the download frequency in the onboard terminal 103, the onboard terminal 103 receives the broadcasted data through the antenna 433, the radio wave receive part 432 and the channel selection part 431 when
10 the broadcast program is broadcasted from SS information distribution part 144 of the information service station 104. The onboard control part 131 decodes the downloaded encrypted information at the onboard security management part 135 by using the user's download cipher key 620. In case that the
15 cryptanalysis is successfully completed, the onboard control part 131 judged that the downloaded data is for its onboard terminal and stores the downloaded data in the onboard memory part 134, and return its terminal number and verification management number indicating that the download data is surely
20 received to the information service station 104 through the onboard transmission and receive part 136.

 The information service station 104 receives a verification information (including the number of the onboard terminal downloading the data and its verification management
25 number) from SS information distribution part 144, and transfer it to SS control part 146. SS control part 146 examines whether the verification management number is identical to that of the information when downloading, and judges that the download operation is completed if the onboard terminal No. 611 in the
30 IC card matches the transmitted onboard terminal number. In case that those does not matches each other or that there is no reply for verification in a definite period of time, an error message

is displayed on SS display part 143, and the screen (5) is got back to display. When completing the download operation, SS control part 146 displays the download completion screen (7) on SS display part 143.

5 When the user selects the verification key on the screen (7), SS control part 146 judges that the download operation was successfully completed, and executes the accounting operation, and then, adds the contents of the download information to the registered data management table 603 of the IC card 437 and
10 ejects the IC card 437 from SS input part 444.

 When the user return the ejected IC card 437 to the onboard terminal 103, the onboard control part 131 judges that the download operation is completed, and then, sets the previous channel number stored in the onboard memory part 131 into the
15 channel selection part 431 in order to switch back to the memorized channel before the downloading operation.

 In case that the user select "Version Upgrade" on the top menu (2) shown in FIG. 8 with his or her finger, SS input part 142 captures the coordinate of the input position on the touch
20 panel 443. SS control part 146 judges from the input coordinate that the menu indicating "Version Upgrade" is selected, and a version-up screen (4) is displayed in the following procedure.

 SS control part 146 finds all the same data as the data with their data No. 631 (321) read out from the IC card 437 and
25 downloaded in the onboard terminal 103 among the data corresponding to the data No. 521 stored on SS data management table 501 in the information service station 104. In addition, the found data are sorted for the individual source data No. 2211, and collecting the individual data numbers 521 having an
30 identical source data No. 2212 and referring to the charge 525 (which is amount of money charged for upgrading a version from its previous version for the individual data. A base charge for

the program is defined for the charge for the version 0.) in SS data management table 501, the total amount of money for the data from the first version 0 to the current version is displayed for the data download charge at SS display part 143.

5 As shown in the screen (4), the program name, the version number and the charge of the data as candidates for version upgrade. In addition, in case that a comment 527 is stored for the latest version for the source data No. 2211 in SS data management table 501, SS control part 146 displays its comment
10 on the comment field. For example, a comment indicating "3D image generation" is displayed on the comment field for "Navigation 1" as the first software.

 The user can select his or her necessary software only by touching the title of the software on the version upgrade
15 screen (4). SS control part 146 identifies the software to be installed on the basis of the position on which the user touch. For example, in case of the screen (4), it is assumed that the user selects the titles of "Navigation 1" and "WWW". As a matter of course, the user is allowed to select plural titles of
20 software. When the user selects plural titles of software and presses "OK" button, SS input part 142 recognizes from the position on the touch panel that the user presses "OK" button, and displays a list of selected titles of software as shown in the screen (5). Later screen operations (5) to (7) and the
25 operation of the service station 104 are the same as those in case for installing new software.

 In the above embodiment, what is described is such a method that, by means that the user visits the information service station 104 and operates interactively the screens in
30 the information service station 104, he or she downloads his or her necessary information into the onboard terminal 103. As for another method, it is allowed that the user can download

his or her necessary information directly from the information service station 104 by operating the onboard terminal 103 while he or she is staying inside the vehicle. A method for downloading an information by means that the user operates the onboard
5 terminal 103 is described below.

FIG. 9 describes screen operations for downloading a necessary information directly from the onboard terminal. In FIG. 9 (a), when the user selects the data already downloaded (for example, WWW and Navigation 1) on the operation screen
10 including the broadcast menu list shown in FIG. 4, and specifies the download button 413, the onboard terminal 103 and the information service station 104 executes the following procedures and downloads the designated data.

When the user selects the download button 413 at the
15 onboard input part 132, the onboard control part 131 directs the channel selection part 431 through the onboard transmission and receive part 135 to switch to the dedicated download channel. In addition, the onboard control part 131, by using this dedicated channel, a communication request for asking whether
20 there is an information service station 104 being able to respond in the neighborhood,
Broadcasts the public-key 620 for the onboard terminal stored in the onboard security management part 135 and the onboard terminal number 611 of the onboard control part 131 with a radio
25 wave through the radio wave transmission and receive part 432.

When the information service station 104 in the neighborhood receives the request from the onboard terminal 103 at SS radio wave communication part 441 of SS data receive part 141, in case that the information service station in the
30 neighborhood is occupied by the execution of the service for another user, the information service station encrypts the data indicating that the information service station is busy and the

unique number of the information service station in SS control
part 146 with the open key 620 received from the onboard terminal
103 and transmits the encrypted information from SS information
distribution part 144. On the other hand, in case that the
5 information service station in the neighborhood is not occupied
by the execution of the service for another user, the
information service station encrypts the message indicating
that the information service station is ready to serve for the
user and the unique number of the information service station
10 in SS control part with the open key 620 received from the onboard
terminal 103 and transmits the encrypted information with a
radio wave from SS information distribution part 144.

The onboard terminal 103 requesting the communication
receives the information from several information service
15 stations 104 at the onboard transmission and receive part 36,
and encodes the received information with its own public-key
620, and then initiates the communication with the information
service station n104 transmitting the message indicating that
its service is available. The onboard terminal 103 encrypts the
20 credit card No. 616 used in payment in the onboard control part
131 and/or the IC card 437 and the data name (for example, WWW
and Navigation 1) of the data which the user specifies on the
screen shown in FIG. 9 (a) for download by using the open key
provided by the information service station 104 with which the
25 onboard terminal wants to communicate, and encrypts again the
unique number of the information service station the user want
to use with the public-key 620 of the onboard terminal 103 and
transmits it.

When SS control part 141 of the information service
30 station answering the message indicating that it can be used
for service receives the data from the onboard terminal 103 in
responsive to the communication request from the onboard

terminal, at first, SS control part decodes the received data with the public-key 620 which is obtained from the onboard terminal 103 with a radio wave previously, and next, judges whether the unique number of the information service station
5 in the encoded data is that for the information service station 104 itself, and if it is not so, SS control part does not proceed the further procedure. On her other hand, If this unique number is that for the information service station itself, SS control part further decodes the data from the onboard terminal 103 with
10 its own public-key, and extracts the credit number 616 provided from the onboard terminal 103 and the data name which the user wants to download.

SS control part 146 searches SS data management table 501 by the title of the software the user selects, and calculates
15 the download charge of the individual software and the total charge by using the method described above. And then, an information indicating such a user's selection defined as "Navigation 1 is ¥3000", "WWW is ¥100" and the total charge is ¥3100 is encrypted with the public key of the onboard terminal
20 and transmitted to the onboard terminal 103.

The onboard terminal 103 decodes the data from the information service station 104 with the public-key 620 and displays a download-on-go message shown in FIG. 9 (b).

And further more, when the information service station
25 104 receives the request for download from the onboard terminal 103, SS control part 146 refers to SS data management table 501 and obtains the memory locations for the software corresponding to be downloaded (for example, "Navigation 1" and "WWW".) A this time, in case that the software to be downloaded is already
30 stored in SS memory part 147, the local memory position 524 can be obtained. In case that the local memory position 524 can not be obtained, the remote memory position 523 broadcasted as index

information 202 can be obtained.

In case that there is an information to be downloaded at the local memory location 524, SS control part 146 gets out an information to be downloaded from a designated location (file name) in SS memory part 504. On the other hand, in case that there is an information to be downloaded at a remote site, SS control part 146 directs SS data receive part 141 to get the information at the remote memory location 523. When SS data receive part 141 receives a remote location 523 and a data receive request from SS control part 146, SS data receive part obtains, from its internal SS wire communication part 442, the information to be downloaded from a remote location (remote information distribution part 401) with FTP protocol through the network 402.

Then, SS control part 146 downloads the file received from the remote site and/or the file stored locally onto user's onboard terminal 103. When SS control part 146 obtains the information specified by the user so as to be downloaded from SS memory part 147 and/or SS data receive part 141, it adds a verification and administration number (64bit fixed-length record) uniquely assigned to the data to be downloaded onto the header of the data and SS security management part 145 encrypts it with a download public-key 620 provided from the onboard terminal. In addition, the encrypted information is modulated in a predefined download frequency and broadcasted at SS information distribution part 144.

In the onboard terminal 103, as the channel selection part 431 of the onboard transmission and receive part 136 is turned for the download frequency, when broadcasting from SS information distribution part 144 at the information service station 104 begins, the onboard terminal receives the data broadcasted through the antenna 433, the radio wave receive part

432 and the channel selection part 431. The onboard control part 131 decodes the downloaded information by using its own cipher key at the onboard security management part 135. At this time, if decoding is successfully completed, the onboard control part
5 judges that the downloaded information is the data directed to itself and stores the data into the onboard memory part 134, and replies its own onboard terminal number and a verification and administration number indicating that the designated data is surely received to the information service station 104
10 through the onboard transmission and receive part 136.

The information service station 104 receives the verification information (the onboard terminal number and the verification and management number for the download operation) from SS information distribution part 144, and transfers it to
15 SS control part 146. SS control part 146 checks whether the verification and management number is identical to the information provided when downloading, and in case that the onboard terminal number 611 transmitted from the onboard terminal 103 coincides the transmitted onboard terminal number,
20 it concludes that the download operation is completed, and transmits a termination report to the onboard terminal 103. In the onboard terminal 103, when completing the download operation, the onboard control part 146 displays the download completion screen as shown in FIG. 9 (c) on the onboard display
25 part 143.

When the user selects the verification key 903 on the download completion screen (c) with the onboard input part 13, the onboard control part 146 reports the user's verification to the information service station 104. The information service
30 station 104 recognizes the successful download operation with the receipt of this user's verification, and applies the charge to the credit number 616 from the onboard terminal 103, and

terminates the communication with the onboard terminal 103. The onboard control part 131 of the onboard terminal 103 also recognizes the termination of the download operation when selecting the verification key 903, and sets the previous
5 channel number stored in the onboard memory part 131 to the channel selection part 431.

According to the present invention, as the program currently broadcasted and information groups including its related data, and the individual data name and index data of
10 the information group already broadcasted and to be broadcasted in the future are broadcasted as digital broadcasting data in multiplex broadcasting, it will be appreciated that a list of data which can not be received by the mobile terminal can be viewed. With this approach, there is such an effect that the
15 data name and its version to which the user can not access easily can be easily obtained, and the user can request to download his or her necessary data among the available data. In addition, as the volume of the index data is smaller enough compared with the source data, various data service can be established without
20 reducing the transmission efficiency of the data broadcasting station.

According to the present invention, as the information service station which receives and stores the data group and index, and distribute them in responsive to the user' request
25 stored can be realized, there is such an effect that the user does not need to memorize all the broadcasting data and the user can download his or her necessary data when he or she needs them.

As the information service station encrypts the data to be downloaded with the cipher key obtained through the
30 communication or the IC card provided by the user, there is such an effect that the download data is not listened to the unintended people and the user can download the data with

security from the information service station through radio wave.

Table 1		Table 2		Table 3		Table 4		Table 5		Table 6		Table 7		Table 8		Table 9		Table 10		Table 11		Table 12		Table 13		Table 14		Table 15		Table 16		Table 17		Table 18		Table 19		Table 20		Table 21		Table 22		Table 23		Table 24		Table 25		Table 26		Table 27		Table 28		Table 29		Table 30		Table 31		Table 32		Table 33		Table 34		Table 35		Table 36		Table 37		Table 38		Table 39		Table 40		Table 41		Table 42		Table 43		Table 44		Table 45		Table 46		Table 47		Table 48		Table 49		Table 50		Table 51		Table 52		Table 53		Table 54		Table 55		Table 56		Table 57		Table 58		Table 59		Table 60		Table 61		Table 62		Table 63		Table 64		Table 65		Table 66		Table 67		Table 68		Table 69		Table 70		Table 71		Table 72		Table 73		Table 74		Table 75		Table 76		Table 77		Table 78		Table 79		Table 80		Table 81		Table 82		Table 83		Table 84		Table 85		Table 86		Table 87		Table 88		Table 89		Table 90		Table 91		Table 92		Table 93		Table 94		Table 95		Table 96		Table 97		Table 98		Table 99		Table 100		Table 101		Table 102		Table 103		Table 104		Table 105		Table 106		Table 107		Table 108		Table 109		Table 110		Table 111		Table 112		Table 113		Table 114		Table 115		Table 116		Table 117		Table 118		Table 119		Table 120		Table 121		Table 122		Table 123		Table 124		Table 125		Table 126		Table 127		Table 128		Table 129		Table 130		Table 131		Table 132		Table 133		Table 134		Table 135		Table 136		Table 137		Table 138		Table 139		Table 140		Table 141		Table 142		Table 143		Table 144		Table 145		Table 146		Table 147		Table 148		Table 149		Table 150		Table 151		Table 152		Table 153		Table 154		Table 155		Table 156		Table 157		Table 158		Table 159		Table 160		Table 161		Table 162		Table 163		Table 164		Table 165		Table 166		Table 167		Table 168		Table 169		Table 170		Table 171		Table 172		Table 173		Table 174		Table 175		Table 176		Table 177		Table 178		Table 179		Table 180		Table 181		Table 182		Table 183		Table 184		Table 185		Table 186		Table 187		Table 188		Table 189		Table 190		Table 191		Table 192		Table 193		Table 194		Table 195		Table 196		Table 197		Table 198		Table 199		Table 200		Table 201		Table 202		Table 203		Table 204		Table 205		Table 206		Table 207		Table 208		Table 209		Table 210		Table 211		Table 212		Table 213		Table 214		Table 215		Table 216		Table 217		Table 218		Table 219		Table 220		Table 221		Table 222		Table 223		Table 224		Table 225		Table 226		Table 227		Table 228		Table 229		Table 230		Table 231		Table 232		Table 233		Table 234		Table 235		Table 236		Table 237		Table 238		Table 239		Table 240		Table 241		Table 242		Table 243		Table 244		Table 245		Table 246		Table 247		Table 248		Table 249		Table 250		Table 251		Table 252		Table 253		Table 254		Table 255		Table 256		Table 257		Table 258		Table 259		Table 260		Table 261		Table 262		Table 263		Table 264		Table 265		Table 266		Table 267		Table 268		Table 269		Table 270		Table 271		Table 272		Table 273		Table 274		Table 275		Table 276		Table 277		Table 278		Table 279		Table 280		Table 281		Table 282		Table 283		Table 284		Table 285		Table 286		Table 287		Table 288		Table 289		Table 290		Table 291		Table 292		Table 293		Table 294		Table 295		Table 296		Table 297		Table 298		Table 299		Table	
---------	--	---------	--	---------	--	---------	--	---------	--	---------	--	---------	--	---------	--	---------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-------	--

WHAT IS CLAIMED IS:

1. A digital broadcasting system comprising
a digital broadcasting transmission apparatus for broadcasting
data groups; and
5 a digital broadcasting receive apparatus for receiving said
data groups directly or indirectly through a data distribution
part,
wherein
said digital broadcasting transmission apparatus has a
10 transmission means for multiplexing and broadcasting ordinary
data to be broadcasted as present programs and index data
defined as identification information of data broadcasted in
past or to be broadcasted in future.
- 15 2. A digital broadcasting system of Claim 1, wherein
said index data includes a data ID of the data broadcasted
in past or to be broadcasted in future, and a remote memory
location from which the data can be downloaded.
- 20 3. A digital broadcasting system of Claim 1 or 2, wherein
said digital broadcasting transmission apparatus adds
distinctive identifiers individually to said ordinary data and
said index data.
- 25 4. A digital broadcasting system of Claim 1, 2 or 3, wherein
said digital broadcasting receive apparatus has a data
separation means for identifying said ordinary data and said
index data separately among the received data groups of digital
broadcasting.
- 30 5. A digital broadcasting system of Claim 4, wherein
aid digital broadcasting receive apparatus has a judge

are switched in responsive to an insert operation of said designated memory media.

18. An information service station storing data groups
5 received in a digital broadcasting and distributing data in responsive to a download request from a mobile terminal, wherein said information service station obtains an individual cipher key for said mobile terminal and encrypts data requested for downloading by said cipher key and sends a encrypted data to
10 a requester.

19. An information service station of Claim 18, wherein a management information including data ID's (number and/or name) of stored data and an internal memory location are stored;
15 and
the data ID's and index data, which are received along with ordinary data as said digital broadcasting data, including external data memory locations for data already broadcasted or to be broadcasted in the future are stored as management data.
20

20. An information service station of Claim 19, wherein said cipher key is obtained from an output of a transmission means of a mobile terminal as a cipher key described in Claim 8.
25

21. An information service station of Claim 19, wherein said cipher key is obtained from an IC card for a mobile terminal as a cipher key described in Claim 16.

22. An information service station of Claim 21, wherein a data ID of data already downloaded by said mobile terminal and stored in said IC card and said management information are
30

compared with each other, and the data not downloaded yet or its version are displayed selectively.

23. An information service station of Claim 22, wherein
5 in case that a download request in terms of selection is issued for data or its version displayed, a download charge is displayed so as to enable to verify a download operation.

24. An information service station of Claim 19, 20, 21, 22
10 or 23, wherein

in case that data requested for download are not located in said internal memory location, said requested data are captured from said external memory location indicated by an index data contained in said requested data and downloaded onto
15 a requester.

ABSTRACT

Ordinary data groups and index information indicating data names and memory locations of broadcasted data are transmitted in multiplex mode from the data broadcasting station 101, and received by the onboard terminal 103 and/or the information service station 104 through the data distribution part 102. The onboard terminal 103 detects the information which it does not hold by referring to the index information, and presents a list of data names at the onboard display part 133. The service station 104 stores separately the data groups and the index information provided from the broadcasting station 104, and in response to the download request from the onboard terminal 103, it examines whether the required data is located in SS memory part 147 by referring to the index data, and captures the required data from external memory locations defined in the index information if the required data is not stored. The download data is encrypted with the cipher key provided by the requester and transmitted through a radio wave.

FIG. 1





FIG. 2(a)*FIG. 2(b)*

202 INDEX INFORMATION

DATA NO.	DATA NAME	MEMORY LOCATION	CHARGE	COMMENT	TIME
1	PROGRAM 1	ftp://H/prog1			
⋮	⋮	⋮			
N	PROGRAM n	ftp://H/progn			

221 222 223 224 225 226


FIG. 2(c)

FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7(a)

CUSTOMER DATA MANAGEMENT TABLE 601

611	ONBOARD TERMINAL NO.	
612	USER NO.	
613	USER NAME	
614	VEHICLE NO.	
615	RENEWAL DATE	
616	CREDIT NO.	
617	USER KEY	
618	ACCESS KEY	
619	ACCESS PASSWORD	
620	DOWNLOAD PUBLIC KEY	
621	NUMBER OF REGISTERED DATA	

FIG. 7(b)

REGISTERED DATA MANAGEMENT TABLE 603

DATA NO.	DATA NAME	Ver.	ACCESS CODE	DATA POINTER

631 (321) 632 (322) 633 634 635

FIG. 8




FIG. 9(a)

DOWNLOAD SOFTWARE SELECTION

PRESENT TIME 13:30			
BROADCASTING TIME	PROGRAM	CHARGE	STATUS
11:00	WWW	¥ 100	UNSETTLED
12:00	NAVIGATION 1	¥ 3000	UNSETTLED
13:00	MAP INFORMATION	¥ 3000	SETTLED
14:00	GASOLINE MILEAGE CALCULATION	¥ 500	UNSETTLED

415

411

412

413

416

RESERVE DELETE DOWNLOAD RETURN




FIG. 9(b)

DOWNLOAD-ON-GO SCREEN

PRESENT TIME 13:30			
BROADCASTING TIME	PROGRAM	CHARGE	STATUS
11:00	WWW	¥ 100	UNSETTLED
12:00	NAVIGATION 1	¥ 3000	UNSETTLED
13:00	MAP	¥ 3000	UNSETTLED
14:00	NAVIGATION 1	¥ 3000	UNSETTLED

901

411

412

413

416

RESERVE DELETE DOWNLOAD RETURN

WWW, NAVIGATION 1
DOWNLOAD-ON-GO

FIG. 9(c)

DOWNLOAD RESULT VERIFICATION SCREEN

PRESENT TIME 13:30			
BROADCASTING TIME	PROGRAM	CHARGE	STATUS
11:00	WWW	¥ 100	UNSETTLED
12:00	NAVIGATION 1	¥ 3000	UNSETTLED
13:00	MAP	¥ 3000	UNSETTLED
14:00	NAVIGATION 1	¥ 3000	UNSETTLED

902

WWW, NAVIGATION 1
TOTAL ¥3100

903

VERIFICATION


411

412

413

416

RESERVE DELETE DOWNLOAD RETURN



Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Japanese Language Declaration (日本語宣言書)

私は、米国法典第35編119条(a)-(d)項又は365条(b)項に基づき下記の、米国以外の国の少なくとも一カ国を指定している特許協力条約365(a)項に基づく国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している、本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示している。

Prior Foreign Application(s)

外国での先行出願

<u>11-227255</u>	<u>Japan</u>
(Number)	(Country)
(番号)	(国名)
(Number)	(Country)
(番号)	(国名)

私は、第35編米国法典119条(e)項に基づいて下記の米国外特許出願規定に記載された権利をここに主張いたします。

<u>(Application No.)</u>	<u>(Filing Date)</u>
(出願番号)	(出願日)

私は、下記の米国法典第35編120条に基づいて下記の米国外特許出願に記載された権利、又は米国を指定している特許協力条約365条(c)に基づき権利をここに主張します。また、本出願の各請求範囲の内容が米国法典第35編112条第1項又は特許協力条約で規定された方法で先行する米国外特許出願に開示されていない限り、その先行米国外出願書提出日より本出願書の日本国内または特許協力条約国際提出日よりの期間中に入手された、連邦規則法典第37編1条56項で定義された特許資格の有無に関する重要な情報について開示義務があることを認識しています。

<u>(Application No.)</u>	<u>(Filing Date)</u>
(出願番号)	(出願日)

<u>(Application No.)</u>	<u>(Filing Date)</u>
(出願番号)	(出願日)

私は、私自身の知識に基づいて本宣言書中で私が行なう表明が真実であり、かつ私の入手した情報と私の信じていることに基づき表明が全て真実であると信じていること、さらに故意になされた虚偽の表明及びそれと同等の行為は米国法典第18編第1001条に基づき、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような故意による虚偽の声明を行なえば、出願した、又は既に許可された特許の有効性が失われることを認識し、よってここに上記のごとく宣誓を致します。

I hereby claim foreign priority under Title 35, United States Code, Section 119 (a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Priority Not Claimed

優先権主張なし

<u>11/August/1999</u>	<input type="checkbox"/>
(Day/Month/Year Filed)	
(出願年月日)	
(Day/Month/Year Filed)	<input type="checkbox"/>
(出願年月日)	

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

<u>(Application No.)</u>	<u>(Filing Date)</u>
(出願番号)	(出願日)

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365(c) of any PCT international application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of application.

<u>(Status: Patented, Pending, Abandoned)</u>
(現況: 特許許可済、係属中、放棄済)

<u>(Status: Patented, Pending, Abandoned)</u>
(現況: 特許許可済、係属中、放棄済)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Japanese Language Declaration (日本語宣言書)

委任状： 私は下記の発明者として、本出願に関する一切の手続きを米特許商標局に対して遂行する弁理士または代理人として、下記の者を指名いたします。（弁護士、または代理人の氏名及び登録番号を明記のこと）

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (list name and registration number)

Thomas E. Beall, Jr., Reg. No.22,410; John R. Mattingly, Reg. No.30,293; Daniel J. Stanger, Reg. No.32,846; Shrinath Malur, Reg. No.34,663; Gene W. Stockman, Reg. No.21,021; Jeffrey M. Ketchum, Reg. No.31,174; and Scott W. Brickner, Reg. No.34,553.

書類送付先

Send Correspondence to:

MATTINGLY, STANGER & MALUR, P.C.

104 East Hume Avenue

Alexandria, Virginia 22301

直接電話連絡先：（氏名及び電話番号）

Direct Telephone Calls to: (name and telephone number)

Telephone: (703) 684-1120

Fax: (703) 684-1157

唯一または第一発明者

Full name of sole or first inventor

Kimiya YAMAASHI

発明者の署名

日付

Inventor's signature

Date

Kimiya Yamaashi 2000.7.7

住所

Residence

Hitachi, Japan

国籍

Citizenship

Japan

私書箱

Post Office Address

c/o Hitachi, Ltd., Intellectual Property Group

New Marunouchi Bldg. 5-1, Marunouchi 1-chome,

Chiyoda-ku, Tokyo 100-8220, Japan

(第二以降の共同発明者についても同様に記載し、署名をすること)

(Supply similar information and signature for second and subsequent joint inventors.)


Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

第二共同発明者	Full name of second joint inventor, if any Masato HORITA		
第二共同発明者の署名	日付	Second inventor's signature <i>Masato Horita</i>	Date 2000. 7. 7
住所	Residence Hitachi, Japan		
国籍	Citizenship Japan		
私書箱	Post Office Address c/o Hitachi, Ltd., Intellectual Property Group New Marunouchi Bldg. 5-1, Marunouchi 1-chome, Chiyoda-ku, Tokyo 100-8220, Japan		
第三共同発明者	Full name of third joint inventor, if any Yukihiko KAWAMATA		
第三共同発明者の署名	日付	Third inventor's signature <i>Yukihiko Kawamata</i>	Date 2000. 7. 7
住所	Residence Hitachi, Japan		
国籍	Citizenship Japan		
私書箱	Post Office Address c/o Hitachi, Ltd., Intellectual Property Group New Marunouchi Bldg. 5-1, Marunouchi 1-chome, Chiyoda-ku, Tokyo 100-8220, Japan		
第四共同発明者	Full name of fourth joint inventor, if any		
第四共同発明者の署名	日付	Fourth inventor's signature	Date
住所	Residence		
国籍	Citizenship		
私書箱	Post Office Address		
第五共同発明者	Full name of fifth joint inventor, if any		
第五共同発明者の署名	日付	Fifth inventor's signature	Date
住所	Residence		
国籍	Citizenship		
私書箱	Post Office Address		

(第六以降の共同発明者についても同様に記載し、署名をすること)

(Supply similar information and signature for sixth and subsequent joint inventors.)

United States Patent & Trademark Office
Office of Initial Patent Examination -- Scanning Division



Application deficiencies were found during scanning:

☐ Page(s) _____ of _____ were not present
for scanning. (Document title)

☐ Page(s) _____ of _____ were not present
for scanning. (Document title)

There are 45 pages of specification enclosed

☐ Scanned copy is best available.

000780-645E960